



Function

Elevator Buffer is the last link

Buffer is the last link in Elevator safety system. Play a buffer role when the accident occurred in the elevator.

Type

Choose buffer which you need

Elevator buffer consists of hydraulic buffers, spring buffers and polyurethane buffers.

Description

Elevator buffers item

Elevator Polyurethane Buffer most widely used. General passenger elevators are using this speed ≤ 1

Size



Full range of all size

A-1	140*200
A-2	100*160
A-3	120*192
A-4	130*208
A-5	150*240
A-10	80*96
A-11	100*120
A-13	160*200
A-14	200*220
A-18	130*158
B-1	162*75

型号	行程	规格	适用电梯 额定速度	总容许质量 P+Qkg	安装尺寸			
					B	b	h	φ
JFDH-A-1	160	Ø 140×200	≤1.0m/s	500~2600	200	160	6	15
JFDH-A-2	80	Ø 100×160	≤1.0m/s	500~1600	128	96	4	14
JFDH-A-3	80	Ø 120×192	≤1.0m/s	800~1980	160	126	4	14
JFDH-A-4	80	Ø 130×208	≤1.0m/s	1010~2820	160	126	4	14
JFDH-A-5	80	Ø 150×240	≤1.0m/s	1000~4000	200	156	4	18
JFDH-A-10	65	Ø 80×96	≤1.0m/s	200~1500	108	80	4	14
JFDH-A-11	65	Ø 100×120	≤1.0m/s	500~2600	128	96	4	14
JFDH-A-13	65	Ø 160×200	≤1.0m/s	1200~6000	200	156	4	18
JFDH-A-14	65	Ø 200×220	≤1.0m/s	290~9860	246	196	4	18
JFDH-A-18	65	Ø 130×158	≤1.0m/s	500~3600	160	126	4	14
JFDH-B-1	60	Ø 162×75	≤1.0m/s	568~2534	205	165	6	18

型号	钢膨胀螺栓规格
JFDH-A-1	M12×95
JFDH-A-2	
JFDH-A-3	
JFDH-A-4	
JFDH-A-18	
JFDH-A-10	
JFDH-A-11	
JFDH-A-5	M16×125
JFDH-A-13	
JFDH-A-14	
JFDH-B-1	



Elevator Buffer B Type

Elevator Buffer A Type

Applicable to the elevator rated speed is less than or equal to 1 meter per second

